

Features and Benefits

Disc Harrows

DH10 Series

| Features | Benefits |
|--|--|
| Working widths | 48", 60" |
| Cat. 1 3-point hitch | Fits Land Pride Quick-Hitch for easy one-person attachment and removal. |
| Weight | 48" - 412 lbs.; 60" - 533 lbs. Heavy construction helps penetrate ground. |
| 2" Square frame tube | Frame tubing is stronger than angle iron. |
| Adjustable gang angles | Cutting aggressiveness can be adjusted on the front and rear up to 21 degrees. |
| 3" x 1 1/2" Gang tube, 1" Sq. gang axles, high carbon steel | High carbon square axles offer great strength in punishing conditions. |
| 16" or 18" Notched or smooth disc blades | Choose notched blades for more aggressive digging and cutting action, or the smooth blades for light tilling. (16" blades only on 48" width) |
| 3/8" Thick bearing hangers | Heavy-duty hangers resist the high torque from U-bolts and/or keep the discs out of the ground. |
| 3/8" Frame side plates | Offer additional strength and reinforcement to the gang tube. |
| Self aligning sealed bearings | Self-aligning bearings offer long life while pounding through hard ground. |

DH15 Series

| Features | Benefits |
|---|---|
| Working widths | 60", 72" & 90" |
| Cat. 1 3-point hitch | Fits Land Pride Quick-Hitch for easy one-person attachment and removal. |
| Weight | 60" - 629 lbs.; 72" - 714 lbs.; 90" - 865 lbs. Heavy construction helps penetrate ground. |
| 2 1/2" Square frame tube | Frame tubing is stronger than angle iron. |
| Adjustable gang angles | Cutting aggressiveness can be adjusted on the front and rear up to 21 degrees. |
| Adjustable gang handles | Gives the user something to hold on to while adjusting gang angles. |
| 3" x 2" Gang tube, 1" Square gang axles, high carbon steel | High carbon square axles offer great strength in punishing conditions. |
| 18" Notched or smooth disc blades | Choose notched blades for more aggressive digging and cutting action, or the smooth blades for light tilling. |
| 3/8" Thick bearing hangers with two 5/8" U-bolts | Heavy-duty hangers resist the high torque from U-bolts and/or keep the discs out of the ground. |
| 1/2" Frame side plates | Offer additional strength and reinforcement to the gang tube. |
| Self aligning sealed bearings | Self-aligning bearings offer long life while pounding through hard ground. |
| Optional scrapers | Scrapers will clean the discs off which can plug up and/or keep the discs out of the ground. |

Designs, specifications, features and information are subject to change without notice.