

Features and Benefits

Rotary Cutters, Single Deck

RCR12 Series

Features	Benefits
Surpassed rugged industry standards	All Land Pride Cutters have been designed and tested and meet rigorous voluntary testing procedures specified by ANSI.
Tractor HP range	20 - 50 HP
3 Year gearbox warranty	Shows our confidence in the gearbox integrity.
Cat. 3 driveline with shear-bolt	Shear bolt offers maximum driveline protection.
Cat. 3 driveline with 2-plate slip-clutch	Slip-clutch driveline offers convenience for continual work.
Floating top link	Permits deck to follow the terrain for an even cut. Two hole position to allow greater lift leverage for smaller tractors.
Clevis Hitch	Cat I, 3-point hitch with floating link for easy hook-up.
Fully welded deck to side skirts	Robotic welded. Adds additional strength.
Round back design	Helps discharge grass better than enclosed or partially enclosed cutters.
1 1/4" - 10" Cutting Height	Cutting height for wide range of cutting conditions.
Skid shoes (Accessory) RCR1260 & RCR1272 only	Provides sidewall reinforcement and helps protect bottom of sidewall.
1/2" x 3" Heat-treated free swinging blades	Free swinging protects from obstructions. Heat-treated offers longer life.
Splined blade bar hub	Allows for tight positive fit of stump jumper and blade bar to gearbox output shaft.
10 Gauge stump jumper	Allows cutter to slide over obstructions protecting the gearbox output shaft.
High blade tip speed	Ensures clean cut.
Laminated tailwheel	Laminated material is long lasting in rough conditions and can't go flat.
Heavy-duty spindle on tailwheel	Tailwheels take a beating, 1 1/4" spindle gives the strength to protect tailwheel assembly.
Rubber guarding	Protect against flying debris.

Designs, specifications, features and information are subject to change without notice.