



# ZG327/ZD321/ZD323 ZD326/ZD331



## SPECIFICATIONS

### Specifications

| Model                                   |                          | ZG327   |                                    | ZD321                             | ZD323                |              |             |
|---|--------------------------|---|------------------------------------|-----------------------------------|----------------------|--------------|-------------|
|   |                          | ZG372P-60   | ZG372RP-60                         | ZD321N-54                         | ZD323-60             |              |             |
| <b>Engine</b>                           | Model                    | Kubota KGZ770-E2-M1   | Kubota KG770-E2-M2                 | Kubota D782-E3-ZD                 | Kubota D902-E3-ZD    |              |             |
|   | Type                     | Gasoline, air-cooled V-Twin with heavy-duty canister air filter |                                    | Diesel, liquid-cooled (3 cyl.)    |                      |              |             |
|   | Max. horsepower (Gross)  | 27HP@3600 rpm   |                                    | 21HP@3200rpm                      | 23HP@3200rpm         |              |             |
|   | Total displacement       | cu.in. (cc)   | 46.9 (768)                         |                                   | 47.5 (778)           | 54.8 (898)   |             |
|   | Starting system          | Key switch  |                                    | Key switch - super glow           |                      |              |             |
| <b>Dimensions</b>                       | Overall length           | in. (mm)  | 87.8 (2230)                        | 87.4 (2220)                       | 86.0 (2185)          | 87.4 (2220)  |             |
|   | Overall width            | (w/ mower)  | in. (mm)                           | 75.2 (1911)                       | 63.1 (1604)          | 67.1 (1704)  | 72.8 (1911) |
|   |                          | (w/o mower)   | in. (mm)                           | 57.5 (1460)                       |                      | 53.7 (1365)  | 57.5 (1460) |
|   | Overall height           | (w/ ROPS upright)   | in. (mm)                           | 75.4 (1915)                       |                      | 61.2 (1555)  |             |
| (w/ ROPS folded)                        |                          | in. (mm)  | 55.5 (1410)                        |                                   | 38.4 (975)           |              |             |
| <b>Wheel base</b>                       |                          | in. (mm)  | 55.5 (1410)                        |                                   | 38.4 (975)           |              |             |
| <b>Tread</b>                            | Front                    | in. (mm)  | 55.5 (1410)                        |                                   | 38.4 (975)           |              |             |
|   | Rear                     | in. (mm)  | 45.3 (1150)                        |                                   | 43.3 (1100)          | 45.3 (1150)  |             |
| <b>Tire size</b>                        | Front                    |   | 15 × 6.0-6 Non-flat                |                                   | 15 × 6.0-6 Pneumatic |              |             |
|   | Rear                     |   | 26 × 12.0-12                       |                                   | 26 × 10.5-12         | 26 × 12.0-12 |             |
| <b>Weight (w/ mower) (without fuel)</b> | lbs. (kg)                | 1473 (668)  | 1577 (715.5)                       | 1517 (688)                        | 1645 (746)           |              |             |
| <b>Transmission system</b>              |                          | 2-HST w/ Gear reduction   |                                    | 2-HST w/ Gear                     |                      |              |             |
| <b>Speed control</b>                    |                          | 2-hand lever  |                                    |                                   |                      |              |             |
| <b>Travel speed range</b>               | Forward                  | mph (km/h)  | 0-10.6 (0-17.0)                    |                                   | 0-9.3 (0-15.0)       |              |             |
|   | Reverse                  | mph (km/h)  | 0-5.3 (0-8.5)                      |                                   | 0-5.2 (0-8.3)        |              |             |
| <b>Brake type</b>                       |                          | Wet multi disks, foot operated                                  |                                    |                                   |                      |              |             |
| <b>PTO</b>                              | Type                     | Shaft drive   |                                    |                                   |                      |              |             |
|   | Clutch type              | Hydraulic independent PTO clutch with wet multi disks           |                                    |                                   |                      |              |             |
|   | PTO brake                | Wet single disk   |                                    |                                   |                      |              |             |
| <b>Mower deck</b>                       | Model                    | RCK60P-327Z   | RCK60P-331Z                        | RCK54P-321Z                       | RCK60P-331Z          |              |             |
|   | Mower lift system        | Hydraulic   |                                    |                                   |                      |              |             |
|   | Mower deck type          | Pro commercial—Fabricated deck                                  |                                    |                                   |                      |              |             |
|   | Deck depth               | in. (mm)  | 6.5 (165)                          | 5.5 (140)                         | 6.0 (152)            | 6.5 (165)    |             |
|   | Belt type                | Multi-Belt  |                                    |                                   |                      |              |             |
|   | Deck steel thickness     | in. (mm)  | 0.18 (4.6), 0.17 (4.2)             |                                   |                      |              |             |
|   | Anti-scalp roller        |   | Rigid                              | Swivel                            | Rigid                | Swivel       |             |
|   | Cutting width of mower   |   | 60 in.                             |                                   | 54 in.               | 60 in.       |             |
|   | Number of blades         |   | 3 blades                           |                                   |                      |              |             |
|   | Cutting height           |   | 1 in. ~ 5 in. / 1/4 in. increments |                                   |                      |              |             |
|   | Mounting system of mower |   | Quick joint, parallel linkage      |                                   |                      |              |             |
|   | Blade tip speed (max.)   |   | 18100 FPM                          | 17100 FPM                         | 17300 FPM            | 18100 FPM    |             |
| <b>Engine stop system</b>               |                          | Key stop  |                                    |                                   |                      |              |             |
| <b>Fuel tank capacity</b>               | gals. (ltrs.)            | 6.1 (23)  |                                    | 12.9 (49)                         |                      |              |             |
| <b>Battery</b>                          |                          | U1L9 (12V, RC: 30 min., CCA: 285, CA: 340)                      |                                    | 51R (12V, RC: 70 min., CCA: 450A) |                      |              |             |
| <b>Alternator capacity</b>              |                          | 13.4 Amps at 12 Volts   |                                    | 14 Amps at 14 Volts               |                      |              |             |
| <b>Water temperature indicator</b>      |                          | -   |                                    | Standard                          |                      |              |             |
| <b>Hour meter</b>                       |                          | Standard  |                                    |                                   |                      |              |             |
| <b>Fuel gauge</b>                       |                          | Electric  |                                    |                                   |                      |              |             |

The company reserves the right to change the above specifications without notice. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. For complete operational information, the operator's manual should be consulted.



# ZG327/ZD321/ZD323 ZD326/ZD331



## SPECIFICATIONS

### Specifications

| Model                                   |                          | ZD326   |                      |                            |
|---|--------------------------|---|----------------------|----------------------------|
|   |                          | ZD326S-60   | ZD326P-60            | ZD326RP-60R                |
| <b>Engine</b>                           | Model                    | Kubota D1005-E3-ZD                                    |                      |                            |
|   | Type                     | Diesel, liquid-cooled (3 cyl.)                        |                      |                            |
|   | Max. horsepower (Gross)  | 26HP @ 3200rpm  |                      |                            |
|   | Total displacement       | 61.1 (1001) cu.in. (cc)                               |                      |                            |
|   | Starting system          | Key switch - super glow                               |                      |                            |
| <b>Dimensions</b>                       | Overall length           | 87.4 (2220) in. (mm)                                  |                      |                            |
|   | Overall width            | (w/ mower)  | 75.2 (1911) in. (mm) |                            |
|   |                          | (w/o mower)   | 63.1 (1604) in. (mm) |                            |
|   | Overall height           | (w/ ROPS upright)                                     | 75.4 (1915) in. (mm) |                            |
| (w/ ROPS folded)                        |                          | 61.2 (1555) in. (mm)                                  |                      |                            |
| <b>Wheel base</b>                       |                          | 55.5 (1410) in. (mm)                                  |                      |                            |
| <b>Tread</b>                            | Front                    | 38.4 (975) in. (mm)                                   |                      |                            |
|   | Rear                     | 45.3 (1150) in. (mm)                                  |                      |                            |
| <b>Tire size</b>                        | Front                    | 15 × 6.0-6 Pneumatic                                  |                      | 15 × 6.0-6 Non-Flat        |
|   | Rear                     | 26 × 12.0-12  |                      |                            |
| <b>Weight (w/ mower) (without fuel)</b> | lbs. (kg)                | 1667 (756)  | 1700 (771)           | 1667 (756)                 |
| <b>Transmission system</b>              |                          | 2-HST w/ Gear   |                      | 2-HST w/ Gear reduction    |
| <b>Speed control</b>                    |                          | 2-hand lever  |                      |                            |
| <b>Travel speed range</b>               | Forward                  | 0-9.3 (0-15.0) mph (km/h)                             |                      | 0-10.6 (0-17.0) mph (km/h) |
|   | Reverse                  | 0-5.2 (0-8.3) mph (km/h)                              |                      | 0-5.3 (0-8.5) mph (km/h)   |
| <b>Brake type</b>                       |                          | Wet multi disks, foot applied, released               |                      |                            |
| <b>PTO</b>                              | Type                     | Shaft drive   |                      |                            |
|   | Clutch type              | Hydraulic independent PTO clutch with wet multi disks |                      |                            |
|   | PTO brake                | Wet single disk                                       |                      |                            |
| <b>Mower deck</b>                       | Model                    | RCK60P-331Z   |                      | RCK60R-331Z                |
|   | Mower lift system        | Hydraulic   |                      |                            |
|   | Mower deck type          | Pro commercial—Fabricated deck                        |                      |                            |
|   | Deck depth               | 6.5 (165) in. (mm)                                    |                      | 5.5 (140) in. (mm)         |
|   | Belt type                | Multi-Belt  |                      |                            |
|   | Deck steel thickness     | 0.18 (4.6), 0.17 (4.2) in. (mm)                       |                      |                            |
|   | Anti-scalp roller        | Swivel  |                      |                            |
|   | Cutting width of mower   | 60 in.  |                      |                            |
|   | Number of blades         | 3 blades  |                      |                            |
|   | Cutting height           | 1 in. ~ 5 in. / 1/4 in. increments                    |                      |                            |
|   | Mounting system of mower | Quick joint, parallel linkage                         |                      |                            |
| Blade tip speed (max.)                  | 18100 FPM                |   | 17100 FPM            |                            |
| <b>Engine stop system</b>               |                          | Key stop  |                      |                            |
| <b>Fuel tank capacity</b>               | gals. (ltrs.)            | 12.9 (49)   |                      |                            |
| <b>Battery</b>                          |                          | 51R (12V, RC: 70 min., CCA: 450A)                     |                      |                            |
| <b>Alternator capacity</b>              |                          | 14 Volts 14 Amps                                      |                      |                            |
| <b>Water temperature indicator</b>      |                          | Standard  |                      |                            |
| <b>Hour meter</b>                       |                          | Standard  |                      |                            |
| <b>Fuel gauge</b>                       |                          | Electric  |                      |                            |

The company reserves the right to change the above specifications without notice. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. For complete operational information, the operator's manual should be consulted.



# ZG327/ZD321/ZD323 ZD326/ZD331



## SPECIFICATIONS

### Specifications

| Model                                   |                           | ZD331                          |   |             |                         |             |
|---|---------------------------|--------------------------------|---|-------------|-------------------------|-------------|
|   |                           | ZD3331P-60                     | ZD3331LP-72   | ZD331RP-60R |                         |             |
| <b>Engine</b>                           | Model                     | Kubota D1005-E3-ZD-2           |   |             |                         |             |
|   | Type                      | Diesel, liquid-cooled (3 cyl.) |   |             |                         |             |
|   | Max. horsepower (Gross)   | 31HP@3000rpm                   |   |             |                         |             |
|   | Total displacement        | 77.0 (1261)                    |   |             |                         |             |
|   | Starting system           | Key switch - super glow        |   |             |                         |             |
| <b>Dimensions</b>                       | Overall length            | in. (mm)                       | 87.4 (2220)   | 91.9 (2335) | 87.4 (2220)             |             |
|   | Overall width             | (w/ mower)                     | in. (mm)  | 63.1 (1604) | 87.6 (2224)             | 63.1 (1604) |
|   |                           | (w/o mower)                    | in. (mm)  |             | 57.5 (1460)             |             |
|   | Overall height            | (w/ ROPS upright)              | in. (mm)  |             | 75.4 (1915)             |             |
|   |                           | (w/ ROPS folded)               | in. (mm)  |             | 61.2 (1555)             |             |
| <b>Wheel base</b>                       |                           | in. (mm)                       | 55.5 (1410)   | 59.8 (1520) | 55.5 (1410)             |             |
| <b>Tread</b>                            | Front                     | in. (mm)                       | 38.4 (975)  | 42.1 (1070) | 38.4 (975)              |             |
|   | Rear                      | in. (mm)                       |   | 45.3 (1150) |                         |             |
| <b>Tire size</b>                        | Front                     |                                | 15 x 6.0-6 Non-Flat                                   |             |                         |             |
|   | Rear                      |                                | 26 x 12.0-12  |             |                         |             |
| <b>Weight (w/ mower) (without fuel)</b> | lbs. (kg)                 |                                | 1715 (778)  | 1770 (803)  | 1681 (763)              |             |
| <b>Transmission system</b>              |                           |                                | 2-HST w/ Gear   |             | 2-HST w/ Gear reduction |             |
| <b>Speed control</b>                    |                           |                                | 2-hand lever  |             |                         |             |
| <b>Travel speed range</b>               | Forward                   | mph (km/h)                     | 0-10.6 (0-17.0)                                       |             |                         |             |
|   | Reverse                   | mph (km/h)                     | 0-5.3 (0-8.5)   |             |                         |             |
| <b>Brake type</b>                       |                           |                                | Wet multi disks, foot operated                        |             |                         |             |
| <b>PTO</b>                              | Type                      |                                | Shaft drive   |             |                         |             |
|   | Clutch type               |                                | Hydraulic independent PTO clutch with wet multi disks |             |                         |             |
|   | PTO brake                 |                                | Wet single disk                                       |             |                         |             |
| <b>Mower deck</b>                       | Model                     |                                | RCK60P-331Z   | RCK72P-331Z | RCK60R-331Z             |             |
|   | Mower lift system         |                                | Hydraulic   |             |                         |             |
|   | Mower deck type           |                                | Pro commercial—Fabricated deck                        |             |                         |             |
|   | Deck depth                | in. (mm)                       | 6.5 (165)   |             | 5.5 (140)               |             |
|   | Belt type                 |                                | Multi-Belt  |             |                         |             |
|   | Deck steel thickness      | in. (mm)                       | 0.18 (4.6), 0.17 (4.2)                                |             |                         |             |
|   | Anti-scalp roller         |                                | Swivel  |             |                         |             |
|   | Cutting width of mower    |                                | 60 in.  | 72 in.      | 60 in.                  |             |
|   | Number of blades          |                                | 3 blades  |             |                         |             |
|   | Cutting height            |                                | 1 in. ~ 5 in. / 1/4 in. increments                    |             |                         |             |
|   | Mounting system of mower  |                                | Quick joint, parallel linkage                         |             |                         |             |
|   | Blade tip speed (max.)    |                                | 18100 FPM   |             | 17100 FPM               |             |
|   | <b>Engine stop system</b> |                                |   | Key stop    |                         |             |
| <b>Fuel tank capacity</b>               | gals. (ltrs.)             |                                | 12.9 (49)   |             |                         |             |
| <b>Battery</b>                          |                           |                                | 51R (12V, RC: 70 min., CCA: 450A)                     |             |                         |             |
| <b>Alternator capacity</b>              |                           |                                | 14 Volts 14 Amps                                      |             |                         |             |
| <b>Water temperature indicator</b>      |                           |                                | Standard  |             |                         |             |
| <b>Hour meter</b>                       |                           |                                | Standard  |             |                         |             |
| <b>Fuel gauge</b>                       |                           |                                | Electric  |             |                         |             |

The company reserves the right to change the above specifications without notice. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. For complete operational information, the operator's manual should be consulted.