



### Front Loader

The LA534A front loader offers a large lifting capacity, perfect for landscaping or light utility work. The curved boom matches the new hood design for a sleek and modern appearance and offers a better field of vision during front loader operations.



### Integrated Loader Valve and Joystick

Loader operations are more convenient with the 4-position valve and control lever. This fully integrated ergonomically positioned valve lets you attach the front-loader and other-front implements quickly and easily.



### New Rod Indicator

The new standard-equipped rod indicator helps the operator easily keep the loader bucket at a level position regardless of the boom height to keep sand, dirt and gravel from spilling when transporting from one location to the next.



### 2-Lever Quick Coupler (optional)

Kubota's quick coupler features two levers to make attach/detach of front attachments quicker and easier.



### Third Function Valve (optional)

The optional 3rd function valve broadens the scope of the front loader operation by enabling use of a grapple bucket and other hydraulically controlled attachments. The 3rd function valve can be activated with buttons located on the grip of the joystick.



### **Hydraulic Spill-Guard (optional)**

The spill-guard tilts the bucket forward as the loader is raised reducing spillage to make filling and dumping easier.



### **Standard Material Bucket 54"**

Two options available: 54" Pin-On Bucket - pins directly onto the loader. 54" 2-Lever Quick Coupler Bucket, 2-Lever Quick Coupler is required to attach to the loader.



### **Light Material Bucket 60"**

Two options available: 60" Pin-On Bucket - pins directly onto the loader. 60" 2-Lever Quick Coupler Bucket, 2-Lever Quick Coupler is required to attach to the loader.



### **Mechanical Snow Blade 60" & 72"**

Available as 2-Lever Quick Coupler Blades. Mount directly to the loader with the 2-Lever Quick Coupler.



### **Hydraulic Snow Blade 60" & 72"**

Available as 2-Lever Quick Coupler Blades. Mount directly to the loader with the 2-Lever Quick Coupler.