

# Grand L60 Series

# Implements

L3560 - L4060 - L4760 - L5060 - L5460 - L6060 Others



## Ballast Box

- Mounted on the three point hitch with sand or gravel to counter balance to the tractor when operating with a front implement.
- Holds a maximum of 845 lbs. of dry sand
- The total weight of the ballast box with sand is 1,000 lbs.
- The ballast box is required for loader applications



## Rotary Tillers

- Available in 60"
- Built-in slip clutch for system protection
- Spring loaded rear shield for smoother ground cover
- Gear box and frame are a one unit assembly for greater durability
- CAT. 1,3-point Hitch



## Rear Mounted Snowblower

- Available in 64" and 74" Cutting Width 2-stage snowblower
- Replaceable Reversible Cutting Edge
- Optional Manual or Hydraulic Chute Rotation Kits Available
- Optional Hydraulic Chute Deflector or Electric Chute Deflector
- Optional Width Extensions (Increases cutting width by 5")



## Front Mounted Snowblower

- Available in 62", 72", 74" and 80"
- Front implement system utilizes a single quick hitch and subframe
- 2-stage snowblower
- Includes blower and chute rotator
- Mid PTO drive system
- Replaceable reversible cutting edge
- Standard hydraulic chute rotation
- Optional hydraulic chute deflector and electric selector valve kit or electric chute deflector
- Optional width extensions (Increases cutting width by 5")
- Requires Mid PTO



## Front Mounted Rotary Sweeper

- Available in both 60" and 72"
- Front implement system which utilizes a single quick hitch and subframe
- Hydraulic angling
- Adjustable suspension
- PTO drive system
- Parking stands
- Optional side caster wheels for detaching
- Optional rubber dust deflector
- Requires Mid PTO



## Front Mounted Blade

- Available in 62", 72", 74" and 80"
- Front implement system utilizes a single quick hitch and subframe
- Front Blade is a heavy duty blade designed for commercial use
- Hydraulic power angle
- HD double bevel cutting edge
- HD replaceable skid shoes
- Optional rubber cutting on 72" blade
- Spring trip with lockout