



Front Loader

The LA534A front loader offers a large lifting capacity, perfect for landscaping or light utility work. The curved boom matches the new hood design for a sleek and modern appearance and offers a better field of vision during front loader operations.



Integrated Loader Valve and Joystick

Loader operations are more convenient with the 4-position valve and control lever. This fully integrated ergonomically positioned valve lets you attach the front-loader and other-front implements quickly and easily.

*B3350HSD model pictured.



New Rod Indicator

The new standard-equipped rod indicator helps the operator easily keep the loader bucket at a level position regardless of the boom height to keep sand, dirt and gravel from spilling when transporting from one location to the next.



2-Lever Quick Coupler (optional)

Kubota's quick coupler features two levers to make attach/detach of front attachments quicker and easier.



Third Function Valve (optional)

The optional 3rd function valve broadens the scope of the front loader operation by enabling use of a grapple bucket and other hydraulically controlled attachments. The 3rd function valve can be activated with buttons located on the grip of the joystick.



Hydraulic Spill-Guard (optional)

The spill-guard tilts the bucket forward as the loader is raised reducing spillage to make filling and dumping easier.



Standard Material Bucket 54"

Two options available: 54" Pin-On Bucket - pins directly onto the loader. 54" 2-Lever Quick Coupler Bucket, 2-Lever Quick Coupler is required to attach to the loader.



Light Material Bucket 60"

Two options available: 60" Pin-On Bucket - pins directly onto the loader. 60" 2-Lever Quick Coupler Bucket, 2-Lever Quick Coupler is required to attach to the loader.



Mechanical Snow Blade 60" & 72"

Available as 2-Lever Quick Coupler Blades. Mount directly to the loader with the 2-Lever Quick Coupler.



Hydraulic Snow Blade 60" & 72"

Available as 2-Lever Quick Coupler Blades. Mount directly to the loader with the 2-Lever Quick Coupler.



Backhoe

The BH77 Backhoe is performance matched with the B50 tractors to deliver more power and greater digging capacity. Additionally, the BH77 backhoe features a curved boom, protected hoses, quick attach/detach mounting system, and optional 6-position mechanical thumb.



Reversible Seat

When its time to switch from loading to back-hoe, simply lift the reversible seat and swivel it to face backhoe controls. The seat also can be adjusted forward and back for optimum operator comfort.

*B3350HSD model pictured.



4-Point Quick-Attach System

With its four connecting points and pin-and-hook type quick-attach system, the backhoe can be attached in minutes without tools.



Front Mounted Blade

60" and 72" front blade.

Front implement system which utilizes a single quick hitch and subframe.

Front Blade is a heavy duty blade designed for commercial use.

Hydraulic power angle is standard on both blades.

HD double bevel cutting edge.

Replaceable skid shoes.

Trip spring lockout design.

Optional rubber cutting edge.



Rear Mounted Snow Blower

51" or 64" Cutting Width 2-stage Snow Blower.

Replaceable Cutting Edge.

Optional Manual or Hydraulic Chute Rotation Kits Available.

Optional drift cutter extensions (increase cutting width by 5").



Ballast Box

Mounted on the three point hitch with sand or gravel to counter balance the tractor when operating with a front implement.

Holds a maximum of 400lbs. (182kg) of dry sand.

The total weight of the ballast box with sand is 500 lbs. (227kg).

The maximum weight allowed on the three point hitch of a B-Series tractor is 500 lbs. (227 kg).

Ballast is required in loader applications.