

SSV Series

Specifications

SSV75



Model			SSV75
Type of operator station			Open CAB / Closed CAB
Engine	Model		V3307-CR-TE4
	Emission certification		Tier 4
	Gross HP (SAE J1995)	HP (kW)/rpm	74.3 (55.4) / 2600
	Net HP (SAE J1349)	HP (kW)/rpm	71.6 (53.4) / 2600
	Peak Torque @1500 rpm	lb-ft (Nm)	196 (265)
	Displacement	cu.in. (cc)	203.3 (3331)
	Cylinders		4
	Bore Stroke	in.(mm)	3.8 (94) × 4.8 (120)
	Aspiration		Turbocharged
Loader performance	Rated operating capacity-50% tipping load		lbs. (kg)
	Tipping load		5380 (2440)
	Breakout force	Bucket	lb. (kgf)
		Lift arm	5884 (2669)
	Lift arm path		4850 (2200)
			Vertical
Power train	Standard tire size		ft.in. (mm)
	Chain size ASA#		12-16.5-10PR
	Travel speed	Low	100
		High	7.4 (11.9)
	Traction force		11.8 (19.0)
	Ground clearance		8494 (3853)
			8.1 (207)
Hydraulic system	Loader hydraulic flow		gpm (/min.)
	Loader hydraulic pressure		20.9 (79.0)
	Aux. hydraulic flow	Standard	psi (kgf/cm2)
		High	3271 (230)
	Service refill capacities		20.9 (79.0)
	Fuel tank		30.4 (115.0)
	Operating weight (Include operator weight 175 lbs.)		gal. ()
			4.2 (16.0)
			gal. ()
			26.9 (102.0)
			lbs. (kg)
			8157 (3700) / 8422 (3820)

Note: The above dimensions are based on the machine with std. tires, skid steer type quick coupler, standard bucket and ROPS/FOPS canopy and cabin. The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, Kubota strongly recommends the use of a Rollover Protective structure (ROPS) and seat belt in almost all applications.