



COMPETITIVE COMPARISON

FEATURE		KUBOTA KX057-4	Bobcat E55	Cat 305E CR	Deere 60G	Takeuchi TB260
Engine	Engine Model	Kubota V2607	Doosan D24NAP	Cat C2.4	Yanmar 4TNV88	Yanmar 4TNV86CT
	Horsepower (Net) HP / rpm	45.2 / 2200	45.7 / 2200	40.2 / 2400	26.8 / 2400	47.6 / 2400
	Displacement cu. in.	159.6	146	110	134	127.6
	Emissions Tier Level (EPA)	Tier 4 Final	Tier 4	Tier 4 Interim	Tier 4 Final	Tier 4 Final
Dimensions	Overall length in.	217.3	208.7	208.26	217.3	218.5
	Overall height in.	100.39	100	100.39	99.6	102.4
	Overall width in.	77.16	77.2	77.95	78.7	78.73
	Tail swing type	Conventional	Conventional	Minimal	Conventional	Conventional
	Tail swing overhang in.	11.44985	13.42	4	16.5	11.815
	Min. ground clearance in.	12.2	---	---	13.38	13
Working Range	Max. digging height in.	225.98	230.3	214.17	236.2	233.9
	Max. dumping height in.	164.56	162.7	154.3	169.68	166.1
	Max. digging radius @ ground in.	240.55	243.7	228.7	---	242.5
	Max. digging depth in.	152.16	154.5	144.48	150.78	153.53
	Max. vertical digging depth	67.3	126	103.5	---	117.3
Hydraulic System	Pump capacity GPM	39.4	36.6	31.5	31.7	45.3
	Number of hydraulic pumps	3	1	---	1	4
	Auxiliary hydraulic flow rate GPM	19.8	20	18.5	23.1	27
	Auxiliary relief psi	2490	3045	2734	---	---
	Maximum arm crowd force lbf	5644	5751	4788	6063	5752
	Max. bucket digging force lbf	11177	8977	10050	8267	12756



COMPETITIVE COMPARISON							
FEATURE		KUBOTA KX057-4	Bobcat E55	Cat 305E CR	Deere 60G	Takeuchi TB260	
Drive System	Traveling speed	mph	1.8 / 3.1	1.9 / 3.1	1.6 / 2.8	1.6 / 2.6	1.7 / 3.0
	Max. traction force	lbf	14480	---	10161	---	13997
	Track shoe width	in.	15.7	15.7	15.7	15.7	15.7
	Ground contact pressure	psi	4.54	4.8	4.1	---	4.51
Swing system	Unit swing speed	rpm	9.3	9	9	9	9.4
	Boom swing angle (L / R)	degree	70 / 55	75 / 50	60 / 50	80 / 60	78 / 55
Blade	Blade width x height	in.	77.2 x 16.1	77.2 x 17.6"	78 x 14.8	78.7 X 15.0	16.9
	Max. lift above ground	in.	17.3	15.1	15.9	18	16.9
	Max. drop below ground	in.	16.1	18.3	21.85	14	16.9
Capacities	Fuel reservoir	gal.	19.8	21.1	16.6	31.7	20.8
	Hydraulic reservoir / system	gal.	11.9 / 20.9	4.0 / 14.5	18.0 / 20.6	21.1 / ---	12.9 / 23.8
Operating weight	Rubber tracks, canopy	lbs.	12200	12313	10836	11349	12509

Comparisons of specifications are based on the latest data available to Kubota at the time of publication.

Kubota reserves the right to change specifications relating to its products without notice.

Competitive information in this section was obtained from competitive websites and product brochures, and is correct to the best of our knowledge.