

# WHF Series

# Specifications

## WHF19-52



Kubota Models	WHF19-52
Model Name	52" Hydro Drive w/ Floating Deck
Engine	Kawasaki FS FX600V
Air Filtration	Canister Air Filter
Lubrication	Full Pressure – Spin on replaceable filter
Displacement	603cc
Starter	Electric
Fuel Capacity	5 Gal.
Cutting Width	52"
Cutting Height	1.5"-5"
Blade Tip Speed @ 3600RPM	18,600 fpm
Deck Construction	Welded 10 gauge w/10 gauge top stiffener and 7 gauge skirts
Discharge Chute	Flexible Molded Polymer
Spindle	1" w/ Maintenance free double sealed bearings
Spindle Bearings	Double Sealed, Precision ground ball bearings
Deck Drive	Warner Mag Stop 175 ft. lb. electric clutch
Transmission Manufacture	Hydro Drive Hydro-Gear® 10cc Pumps w/ Parker wheel motor
Brake	Hydrostatic, Dynamic Braking w/Parking Brake
Speed	6.7 mph
Tires Front Rear	11x4.0"-5" Pneumatic 18"x 7.5"-8" 4 ply
Length	80.7"
Height	43"
Weight/Wet	785 lbs.

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional and not standard equipment. Please consult your local Kubota dealer for warranty, safety or product information. For your safety, Kubota strongly recommends the use of a seat belt in all applications.