

## COMPETITIVE COMPARISON

| MODEL                |  | Kubota<br>BX1870         | Kubota<br>BX2370         | John Deere<br>1023E        | New Holland<br>Boomer 20 | Massey Ferguson<br>GC2400 | Kubota<br>BX2670         | John Deere<br>1025R        | Massey Ferguson<br>GC2600 | New Holland<br>Boomer 25 |
|----------------------|--|--------------------------|--------------------------|----------------------------|--------------------------|---------------------------|--------------------------|----------------------------|---------------------------|--------------------------|
| Engine               | Manufacturer                                     | Kubota                   | Kubota                   | Yanmar                     | Mitsubishi               | Iseki                     | Kubota                   | Yanmar                     | Iseki                     | Mitsubishi               |
|                      | Type   | Diesel                   | Diesel                   | Diesel                     | Diesel                   | Diesel                    | Diesel                   | Diesel                     | Diesel                    | Diesel                   |
|                      | Gross Engine HP (kw)                             | 18 (13.4)                | 23 (17.2)                | 22.4 (16.5)                | 23 (16.9)                | 22.5 (17)                 | 25.5 (19.0)              | 23.9 (17.8)                | 25 (18.6)                 | 27 (19.9)                |
|                      | PTO HP (kw)                                      | 13.7 (10.2)              | 17.7 (13.2)              | 15.3 (11.4)                | 16.5 (12.1)              | 18.7 (14)                 | 19.5 (14.5)              | 18 (13.4)                  | 19.6 (14.6)               | 19.9 (14.7)              |
|                      | Rated Engine Speed rpm                           | 3200                     | 3200                     | 3200                       | 2700                     | 2600                      | 3200                     | 3200                       | 3000                      | 2700                     |
|                      | Cylinders/Displacement cu.in. (liters)           | 3/43.9 (719)             | 3/54.8 (.898)            | 3/55 (.903)                | 3/68.7 (1.1)             | 3/68.7 (1.123)            | 3/61.1 (1.001)           | 3/68.1 (1.116)             | 3/68.5 (1.123)            | 3/80.4 (1.3)             |
|                      | Engine Torque@ rated speed ft./lb. (N/m)         | 33 (4.58)                | 41.7 (5.5)               | 36.3 (49.2)                | –                        | –                         | 46.5 (62.5)              | 40/7 (55.2)                | –                         | –                        |
|                      | Fuel Tank Cap US Gal. (L) (Open; Cab)            | 6.6 (25)                 | 6.6 (25)                 | 5.6 (21.2)                 | 6.6 (25)                 | –                         | 6.6 (25)                 | 5.6 (21.2)                 | 6.6 (25)                  | 6.6 (25)                 |
| Electrical           | Battery Size (CCA)                               | 450                      | 540                      | 500                        | 560                      | 433                       | 540                      | 500                        | 433                       | 560                      |
|                      | Alternator (12 volt, amp)                        | 40                       | 40                       | 40                         | 50                       | 40                        | 40                       | 40                         | 40                        | 50                       |
| Transmission         | Std. Transmission; Forward/Reverse               | Hydrostatic - 2 range    | Hydrostatic - 2 range    | Hydrostatic - 2 range      | Hydrostatic - 2 range    | Hydrostatic - 2 range     | Hydrostatic - 2 range    | Hydrostatic - 2 range      | Hydrostatic - 2 range     | Hydrostatic - 2 range    |
|                      | Brakes   | Multi wet disc           | Multi wet disc           | Wet disk (left hand pedal) | Wet disc                 | Wet disc                  | Wet disc                 | Wet disk (left hand pedal) | Wet disc                  | Wet disc                 |
|                      | Steering   | Power                    | Power                    | Power                      | Power                    | Power                     | Power                    | Power                      | Power                     | Power                    |
|                      | Axle Capacity Front, lb. (kg)<br>Rear, lb. (kg)  | 1630 (740)<br>2120 (960) | 1630 (740)<br>2120 (960) | 1252 (568)<br>2077 (942)   | –<br>–                   | –<br>–                    | 1630 (740)<br>2120 (960) | 1253 (568)<br>2078 (942)   | –<br>–                    | –<br>–                   |
| Hydraulics           |  | 2                        | 2                        | 2                          | 2                        | 2                         | 2                        | 2                          | 2                         | 2                        |
|                      | Remote Control Valves Available                  |                          |                          |                            |                          |                           |                          |                            |                           |                          |
| 3-point Hitch        | Type   | Category 1               | Category 1               | Limited Category 1         | Category 1               | Category 1                | Category 1               | Limited Category 1         | Category 1                | Category 1               |
|                      | Lift Capacity (24-in. behind link arms) lb. (kg) | 680 (310)                | 680 (310)                | 681 (309)                  | 700 (318)                | 550 (249)                 | 680 (310)                | 681 (309)                  | 550 (249)                 | 700 (318)                |
|                      | Lift Capacity @ lift links ends lb. (kg)         | 1210 (550)               | 1210 (550)               | –                          | 1433 (650)               | 1191 (540)                | 1210 (550)               | –                          | 1191 (540)                | 1433 (650)               |
| Power Take-Off (PTO) | Standard   | Rear 540/Mid 2500        | Rear 540/Mid 2500        | Rear 540/Mid 2100          | Rear 540/Mid 2000        | Rear 540/Mid 2000         | Rear 540/Mid 2500        | Rear 540/Mid 2100          | Rear 540/Mid 2000         | Rear 540/Mid 2000        |
|                      | Control  | Independent              | Independent              | Independent                | Independent              | Mechanical                | Independent              | Independent                | Mechanical                | Independent              |
|                      | Clutch   | Wet hydraulic            | Wet hydraulic            | Wet disc                   | Electro-hydraulic        | Wet, multi-disc           | Wet hydraulic            | Wet disc                   | Wet, multi-disc           | Electro-hydraulic        |
| Operator Station     | Rollover Protective Structure                    | Yes                      | Yes                      | Yes                        | Yes                      | Yes                       | Yes                      | Yes                        | Yes                       | Yes                      |
|                      | Rigid- Foldable - Telescopic                     | Foldable                 | Foldable                 | Foldable                   | Foldable                 | Rigid                     | Foldable                 | Foldable                   | Rigid                     | Foldable                 |
|                      | Platform - Flat/Straddle                         | Flat                     | Flat                     | One-piece semi flat        | Flat                     | Semi flat                 | Flat                     | One-piece semi flat        | Semi flat                 | Flat                     |
| Dimensions           | Wheelbase in. (mm)                               | 52.8 (1340)              | 55.1 (1400)              | 57.1 (1450)                | –                        | 57.1 (1450)               | 55.1 (1400)              | 57.1 (1450)                | 57.1 (1450)               | –                        |
|                      | Front Tread in. (mm)                             | 34.6 (880)               | 36.6 (930)               | 36.1 (918)                 | –                        | –                         | 36.6 (930)               | 36.1 (918)                 | –                         | –                        |
|                      | Front Axle Clearance in. (mm)                    | 9.0 (230)                | 8.7 (220)                | 7.7 (195)                  | –                        | 6.7 (170)                 | 8.7 (220)                | 7.7 (195)                  | 6.7 (170)                 | –                        |
|                      | Turning Radius w/o Brakes ft. (m)                | 7.2 (2.2)                | 7.5 (2.3)                | 7.4 (2.25)                 | –                        | 8.4 (2.6)                 | 7.5 (2.3)                | 7.4 (2.25)                 | 8.4 (2.6)                 | –                        |
|                      | Tractor Weight                                   | 1345 (610)               | 1410 (640)               | 1345 (610)                 | 1702 (772)               | 1433 (650)                | 1466 (665)               | 1444 (665)                 | 1433 (650)                | 1702 (772)               |
| Standard Tires       | Front  | 16x7.5-8 Turf/Bar/Ind    | 18x8.5-10 Turf/Bar/Ind   | 18x8.5-10 R4               | 18x8.5-8.4PR Turf        | 18x8.5-10 R1              | 18x8.5-10 Turf/Bar/Ind   | 18x8.5-10 R4               | 18x8.5-10 R1              | 18x8.5-8.4PR Turf        |
|                      | Rear   | 24x12-12 Turf/Bar/Ind    | 26x12.0-12 Turf/Bar/Ind  | 26x12-12 R4                | 26x12-12 4PR Turf        | 26x12.00-12 R1            | 26x12.0-12 Turf/Bar/Ind  | 18x8.5-10 R4               | 26x12.00-12 R1            | 26x12-12 4PR Turf        |

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge.

Kubota reserves the right to change the specifications relating to its products without notice.